



US009409725B2

(12) **United States Patent**
Stikkelorum

(10) **Patent No.:** **US 9,409,725 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **DEVICE FOR SORTING PRODUCTS**

(56) **References Cited**

(75) Inventor: **Simon Gerardus Stikkelorum**, Haps
(NL)

U.S. PATENT DOCUMENTS

(73) Assignee: **VANDERLANDE INDUSTRIES B.V.**,
Veghel (NL)

4,846,335 A * 7/1989 Hartlepp 198/370.04
5,732,439 A * 3/1998 Cipolla 15/334
6,193,074 B1 * 2/2001 Baum et al. 209/606

(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 410 days.

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **13/696,108**

EP 0960838 A1 12/1999
EP 1411008 A1 4/2004
EP 1447359 A2 8/2004

(22) PCT Filed: **Apr. 29, 2011**

OTHER PUBLICATIONS

(86) PCT No.: **PCT/NL2011/050295**

Search Report for Dutch Patent Application No. 2004675; Feb. 9,
2011.

§ 371 (c)(1),

(2), (4) Date: **Feb. 4, 2013**

(Continued)

(87) PCT Pub. No.: **WO2011/139147**

Primary Examiner — Gene Crawford

Assistant Examiner — Lester Rushin

PCT Pub. Date: **Nov. 10, 2011**

(74) *Attorney, Agent, or Firm* — Barnes & Thornburg LLP

(65) **Prior Publication Data**

US 2013/0126304 A1 May 23, 2013

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

May 6, 2010 (NL) 2004675

(51) **Int. Cl.**

B65G 47/40 (2006.01)

B65G 47/96 (2006.01)

(52) **U.S. Cl.**

CPC **B65G 47/40** (2013.01); **B65G 47/962**
(2013.01)

(58) **Field of Classification Search**

CPC B65G 47/962

USPC 198/370.04, 370.01, 377.02, 370.03,
198/621.3; 209/707

See application file for complete search history.

A device for sorting products having carrier units arranged adjacent to each other and conveying means for supporting and conveying the carrier units. Each carrier unit has a support platform, support means for supporting the support platform, leg members supported by the conveying means and tiltably supporting the support means, and tilting means for tilting the support means relative to each other about a tilt axis extending parallel to the conveying path. The tilting means has at least one cam and drive means having an electric motor supported by the conveying means for rotating the at least one cam relative to the leg members about an axis of rotation, as well as a camway which is rigidly connected to the support means and with which the at least one cam mates upon rotation of the at least one cam about the axis of rotation. The tilt axis is located between the axis of rotation and the support platform.

14 Claims, 5 Drawing Sheets

